



Secure, Convenient, and Multi-Functional

MinMoe Temperature Screening Terminal A70 Series

Hikvision knows that it is always crucial for businesses to maximize efficiency – and that guides us when designing products and solutions with multiple functionalities. As thermographic technology is integrated into the everyday access control solution, now you have the classic solution that also works under the new norms. Check out the following product for this cost-effective temperature screening solution.

- ◆ **Thermographic technology**
- ◆ **Displays real-time skin-surface temperature**
- ◆ **Face mask detection**
- ◆ **Flexible deployment**





DS-K1TA70MI-T

MinMoe Temperature Screening Terminal

- Detection temperature range: 30 – 45°C, accuracy: 0.1°C, deviation: ±0.5°C
- Authentication distance: 0.3 – 1.8 m
- Max. capacity: 6,000 faces, 6,000 MIFARE cards

DS-DM0710BL

Table Bracket (Optional)

- Table Mounting for DS-K1TA70MI-T
- Dimension (WxHxD): 192 x 353 x 195 mm



DS-KAB671-B

Floor-standing Bracket (Optional)

- Mounting pole for DS-K1TA70MI-T
- Dimension (WxHxD): 98.5 x 1342 x 225 mm

Various Application Scenarios



Schools



Factories



Offices



Retailers

Note1: Indoor installation is recommended for better temperature accuracy (without wind).

Note2: Hikvision's temperature screening thermographic cameras are designed for the detection of skin-surface temperatures so as to achieve rapid preliminary screening in public areas. Actual core body temperatures should be further confirmed using clinical measurement devices. Under any circumstances, it is highly recommended to use Hikvision's thermographic cameras in accordance with local laws and regulations.

Hikvision Europe

Dirk Storklaan 3
2132 PX Hoofddorp
The Netherlands
T +31 23 5542770
info.eu@hikvision.com
www.hikvision.com

